

SPRO

POE INJECTOR

Model Number: POEINJECTOR



KEY-FEATURES

- Support 1*10/100/1000M PoE port + 1*10/100/1000M network port
- Comply with IEEE802.3, IEEE802.3u, IEEE802.3ab standards
- Ethernet port supports 10/100/1000M self-adaptation
- Support port auto flip (Auto MDI/MDIX)
- Support IEEE802.3af (15.4W), IEEE802.3at (30w)
- Support AC 100-240 V input
- -10 to 50°C operating temperature
- Support wall mount

INPUT/OUTPUT INTERFACE

Power	AC INPUT (100-240V)
Ethernet	1*PoE port 1*RJ45 network port

PROTOCOL STANDARD

Network Protocol	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3ab (Gigabit Ethernet) IEEE802.3x (flow control)
Network Medium	10Base-T : Cat3, 4, 5 or above UTP/STP (≤100m) 100Base-TX : Cat5 or above UTP/STP (≤100m) 1000BASE-TX: Category Cat5 and above UTP (≤100 meters)

(continued)

Industry Standard

EMI: FCC Part 15 CISPR (EN55032) class A
EMS: EN61000-4-2 (ESD)、EN61000-4-4 (EFT)
EN61000-4-5 (Surge)
Shock: IEC 60068-2-27
Free Fall: IEC 60068-2-32
Vibration: IEC 60068-2-6

ENVIRONMENTAL STANDARDS

Working Environment

Working temperature: -10~50°C
Storage temperature: -40~70°C
Operating humidity: 90% maximum relative humidity, non-condensing
Storage Humidity: 95% relative humidity maximum, non-condensing
Working Height: Up to 10,000 ft (3,000 m)
Storage Height: Up to 10,000 ft (3,000 m)

FUNCTION INDICATION

Indicator Light

Power (Power Indicator)

PHYSICAL SPECIFICATIONS

Structure Size

Product size: 142* 55*40mm
Packing size: 210* 160*55mm
Product net weight: 0.2KG
Product gross weight: 0.4KG

Packing List

1 power supply
1 power cord
1 manual
1 certificate



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved