



SWITCH-16P

16 PORT POE FIBER SWITCH

Key Features:

- 16 port PoE
- Total power budget : 250W
- Plug & Play
- Status LEDs
- PSU included

SPECIFICATIONS

Model Number	SWITCH-16P	
Type	16 Port Switch	
Interface	Downlink ports	1-16: 10/100Mbps RJ45 Ports
	Uplink port	17 -18 : 2 GE RJ45+2GE SFP (Combo)
POE Power Supply	Max PoE output	30W
	Total power supply	250W
	Priority Function	Support
LEDs	Power Link/activity	
Transfer Method	Store-and-Forward	
Advanced Feature	IEEE802.3x Flow Control for Full- Duplex Mode & Backpressure for Half-Duplex Mode	
Performance	Switching Capacity	7.2 Gbps
	Packet Forwarding Rate	5.36 Mbps
	Mac Address Table	8K
Standards & Protocols	IEEE802.3i 10 BASE-T	
	IEEE802.3u 100 BASE-TX	
	IEEE802.3ab 1000 BASE-T	
	IEEE802.3z 1000 BASE-LX	

	IEEE802.3x Flow Control
	IEEE802.3af Power over Ethernet
	IEEE802.3at Power over Ethernet
	IEEE802.3az EEE
Power Input	AC 100-240V 50/60HZ
Dimensions	440mm(L) *285mm(W) *44mm(H)
Cables	UTP category 5 or above cable
Operating Temperature	0 ~ 40 °C
Operating Humidity	10% ~ 90% RH non-condensing
Storage Temperature	~ 20 ~ 75 °C
Storage Humidity	5% ~ 95% RH non-condensing



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved